

ABSTRACT

A method and apparatus includes a plurality of processor groups each having a plurality of processor switch chips each having a plurality of processors and a processor crossbar, each processor connected to the processor crossbar; a plurality of switch groups each having a plurality of switch crossbar chips each having a plurality of switch crossbars each connected to a processor crossbar in each processor group, wherein no two switch crossbars in a switch group are connected to the same processor crossbar; a plurality of memory groups each having a plurality of memory switch chips each having a plurality of memory controllers and a memory crossbar, each memory controller connected to the memory crossbar, each memory crossbar in each memory group connected to all of the switch crossbars in a corresponding one of the switch groups, wherein no two memory groups are connected to the same switch group; and a plurality of memory chips each having a plurality of memory tracks each having a plurality of shared memory banks, each memory track connected to a different one of the memory controllers.

15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500